

Interflon Grease HTG (aerosol)

Version number:
4.6
Replaces version: (3)

Date of issue
2021-01-07

Revision:
2021-01-07.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	Interflon Grease HTG (aerosol)
Registration number (REACH)	not relevant (mixture)
Unique formula identifier - UFI	YV00-N0AW-S00Y-9KMT

1.2 Relevant identified uses of the substance or mixture and uses advised against

Scope	lubricant
-------	-----------

1.3 Details of the supplier of the safety data sheet

Interflon BV
Belder 47
4704 RK Roosendaal
Netherlands

Telephone: +31 (0)165 553911
e-mail: Service@interflon.com
Website: www.interflon.com

e-mail (competent person) Service@interflon.com (Service lab)

1.4 Emergency telephone number

Poison centre					
Country	Name	Postal code/ city	Telephone	Telefax	Opening hours
Ireland	Poisons Information Centre of Ireland	9 Dublin	Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) Health-care Professionals: +353 (1) 809 2566 (24 hour service)		Mon - Fri 12:00 AM - 11:00 PM

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	1	Aerosol 1	H222,H229
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

Interflon Grease HTG (aerosol)

Version number:

4.6

Replaces version: (3)

Date of issue

2021-01-07

Revision:

2021-01-07.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- Signal word. danger

- Pictograms

GHS02, GHS07



- Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

- Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P312	Call a POISON CENTRE/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to industrial combustion plant.

Additional labelling according to Directive 75/324/EEC relating to aerosol dispensers

Extremely flammable. Pressurized container: may burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- Hazardous ingredients for labelling

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics, Hydrocarbons, C6, isoalkanes, <5% n-hexane

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Product description

Mixture of synthetic oils, thickener, additives and Micpol®

Interflon Grease HTG (aerosol)

Version number:

4.6

Replaces version: (3)

Date of issue

2021-01-07

Revision:

2021-01-07.

Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
Propane	CAS No 74-98-6 EC No 200-827-9 Index No 601-003-00-5 REACH Reg. No 01-2119486944-21-xxxx	10 – < 25	Flam. Gas 1 / H220 Press. Gas L / H280	
butane	CAS No 106-97-8 EC No 203-448-7 Index No 601-004-00-0 REACH Reg. No 01-2119474691-32-xxxx	10 – < 25	Flam. Gas 1 / H220 Press. Gas C / H280	C(a) K(b)
isobutane	CAS No 75-28-5 EC No 200-857-2 Index No 601-004-00-0 REACH Reg. No 01-2119485395-27-xxxx	10 – < 25	Flam. Gas 1 / H220 Press. Gas C / H280	C(a) GHS-HC U
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	CAS No 64742-49-0 EC No 927-510-4 REACH Reg. No 01-2119475133-43-xxxx 01-2119475515-33-xxxx 01-2119485645-26-xxxx 01-2119666169-27-xxxx	10 – < 25	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Acute 1 / H400 Aquatic Chronic 2 / H411	
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC No 927-241-2 REACH Reg. No 01-2119471843-32-xxxx	7.5 – < 10	Flam. Liq. 3 / H226 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 3 / H412	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	CAS No 64742-49-0 EC No 931-254-9 REACH Reg. No 01-2119484651-34-xxxx	7.5 – < 10	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	

Notes

C(a): Mixture of isomers

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)

Interflon Grease HTG (aerosol)**Version number:**

4.6

Replaces version: (3)

Date of issue

2021-01-07

Revision:

2021-01-07.

Notes

- K(b): The classification as a carcinogen or mutagen is not required. The substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-) P210-P403 should apply
- U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Interflon Grease HTG (aerosol)**Version number:**

4.6

Replaces version: (3)

Date of issue

2021-01-07

Revision:

2021-01-07.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Conditions of storage

Store in accordance with local/regional/national/international regulations. Keep container tightly closed and in a well-ventilated place.

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

Interflon Grease HTG (aerosol)

Version number:
4.6
Replaces version: (3)

Date of issue
2021-01-07

Revision:
2021-01-07.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
IE	n-butane	106-97-8	OELV	1,000							S.I. No. 619 of 2001
IE	propane	74-98-6	OELV							asphyx	S.I. No. 619 of 2001
IE	isobutane	75-28-5	OELV	1,000							S.I. No. 619 of 2001

Notation

asphyx simple asphyxiants
 Ceiling-C ceiling value is a limit value above which exposure should not occur
 STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
 TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
 time-weighted average (unless otherwise specified)

no data available

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	DNEL	2,085 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	DNEL	300 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics		DNEL	871 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics		DNEL	77 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	DNEL	5,306 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	DNEL	13,964 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

8.2 Exposure controls

Interflon Grease HTG (aerosol)**Version number:**

4.6

Replaces version: (3)

Date of issue

2021-01-07

Revision:

2021-01-07.

General safety precautions

Use only in well-ventilated areas.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
Do not eat, drink and smoke in work areas.

Individual protection measures (personal protective equipment)**Eye/face protection**

Wear eye/face protection. Use safety goggle with side protection.

Skin protection**- Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloroprene (chlorobutadiene) rubber. PVC: polyvinyl chloride.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

Not required.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

Physical state	aerosol (spray aerosol)
Colour	brown
Odour	Like oil

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	-0 °C at 1,013 hPa
Flash point	>300 °C
Evaporation rate	not determined
Flammability (solid, gas)	flammable aerosol in accordance with GHS criteria

Interflon Grease HTG (aerosol)

Version number:
4.6
Replaces version: (3)

Date of issue
2021-01-07

Revision:
2021-01-07.

Explosive limits

- Lower explosion limit (LEL)	1.5 vol%
- Upper explosion limit (UEL)	10 vol%
Vapour pressure	3,800 hPa at 20 °C
Density	1.03 g/cm ³ at 20 °C
Vapour density	this information is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	>400 °C (auto-ignition temperature (liquids and gases))

Viscosity

- Kinematic viscosity	631,068 mm ² /s at 20 °C
- Dynamic viscosity	650 Pa s at 20 °C
Explosive properties	none
Oxidising properties	none

9.2 Other information

Propellant content	50.99 %
--------------------	---------

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidisers

Interflon Grease HTG (aerosol)

Version number:
4.6
Replaces version: (3)

Date of issue
2021-01-07

Revision:
2021-01-07.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if inhaled.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	EL50	1.6 mg/l	aquatic invertebrates	21 d
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	EC50	0.23 mg/l	aquatic invertebrates	21 d

Interflon Grease HTG (aerosol)

Version number:

4.6

Replaces version: (3)

Date of issue

2021-01-07

Revision:

2021-01-07.

12.2 Persistence and degradability

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	oxygen depletion	83 %	16 d		ECHA
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics		oxygen depletion	8 %	3 d		ECHA
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics		carbon dioxide generation	0 %	3 d		ECHA
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	oxygen depletion	83 %	10 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butane	106-97-8		1.09 (pH value: 7, 20 °C)	
Propane	74-98-6		1.09 (pH value: 7, 20 °C)	
isobutane	75-28-5		1.09 (pH value: 7, 20 °C)	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	501.2	3.6 (pH value: 7, 20 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

Interflon Grease HTG (aerosol)

Version number:
4.6
Replaces version: (3)

Date of issue
2021-01-07

Revision:
2021-01-07.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes

- Product
20 01 26* oil and fat other than those mentioned in 20 01 25


Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

- | | |
|--|--|
| 14.1 UN number | 1950 |
| 14.2 UN proper shipping name | AEROSOLS |
| 14.3 Transport hazard class(es) | |
| Class | 2 (gases) (aerosol) |
| Subsidiary risk(s) | 2.1 (flammable) |
| 14.4 Packing group | not assigned to a packing group |
| 14.5 Environmental hazards | non-environmentally hazardous acc. to the dangerous goods regulations |
| 14.6 Special precautions for user | |
| | Provisions for dangerous goods (ADR) should be complied within the premises. |
| 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code | |
| | The cargo is not intended to be carried in bulk. |

Information for each of the UN Model Regulations**Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)**

UN number	1950
Proper shipping name	AEROSOLS
Class	2
Classification code	5F
Danger label(s)	2.1
	
Special provisions (SP)	190, 327, 344, 625

Interflon Grease HTG (aerosol)

Version number:

4.6

Replaces version: (3)

Date of issue

2021-01-07

Revision:

2021-01-07.

Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D

International Maritime Dangerous Goods Code (IMDG)

UN number	1950
Proper shipping name	AEROSOLS
Class	2.1
Marine pollutant	-
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	-

International Civil Aviation Organization (ICAO-IATA/DGR)

UN number	1950
Proper shipping name	Aerosols, flammable
Class	2.1
Danger label(s)	2.1



Special provisions (SP)	A145, A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
Propane	flammable / pyrophoric		R40	40
butane	flammable / pyrophoric		R40	40
isobutane	flammable / pyrophoric		R40	40

Interflon Grease HTG (aerosol)

Version number:

4.6

Replaces version: (3)

Date of issue

2021-01-07

Revision:

2021-01-07.

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	flammable / pyrophoric		R40	40
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	flammable / pyrophoric		R40	40
Hydrocarbons, C6, isoalkanes, <5% n-hexane	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
Hydrocarbons, C6, isoalkanes, <5% n-hexane	flammable / pyrophoric		R40	40

Legend

R3

- Shall not be used in:
 - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
- Articles not complying with paragraph 1 shall not be placed on the market.
- Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
 - can be used as fuel in decorative oil lamps for supply to the general public, and,
 - present an aspiration hazard and are labelled with R65 or H304,
- Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
- Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
 - lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage';
 - grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage';
 - lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
- No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.
- Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.

R40

- Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:
 - metallic glitter intended mainly for decoration,
 - artificial snow and frost,
 - 'whoopie' cushions,
 - silly string aerosols,
 - imitation excrement,
 - horns for parties,
 - decorative flakes and foams,
 - artificial cobwebs,
 - stink bombs.
- Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:
 - 'For professional users only'.
- By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
- The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

Interflon Grease HTG (aerosol)

Version number:
4.6
Replaces version: (3)

Date of issue
2021-01-07

Revision:
2021-01-07.

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

Seveso Directive

2012/18/EU (Seveso III)				
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
P3a	flammable aerosols (containing Flam. Gas or Flam. Liq.)	150	500	46)

Notation

46) 'flammable' aerosols category 1 or 2, containing flammable gases category 1 or 2 or flammable liquids category 1

Note: qualifying quantity = net

Deco-Paint Directive (2004/42/EC)

VOC content	81.78 %
-------------	---------

Directive on industrial emissions (VOCs, 2010/75/EU)

VOC content	80.93 %
-------------	---------

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

none of the ingredients are listed

Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

none of the ingredients are listed

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	all ingredients are listed or exempt from listing
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Interflon Grease HTG (aerosol)

Version number:
4.6
Replaces version: (3)

Date of issue
2021-01-07

Revision:
2021-01-07.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
log KOW	n-Octanol/water

Interflon Grease HTG (aerosol)

Version number:

4.6

Replaces version: (3)

Date of issue

2021-01-07

Revision:

2021-01-07.

Abbr.	Descriptions of used abbreviations
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
Press. Gas	Gas under pressure
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
S.I. No. 619 of 2001	Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
SVHC	Substance of Very High Concern
TWA	Time-weighted average
UFI	Unique formula identifier
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.

Interflon Grease HTG (aerosol)**Version number:**

4.6

Replaces version: (3)

Date of issue

2021-01-07

Revision:

2021-01-07.

Code	Text
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.