

## Technical Data Sheet

# Interflon Fin Clean All<sup>2</sup>

### Deep cleaning alkaline label-free cleaner with “1001” applications

Versatile, highly alkaline, label-free deep enzymatic cleaner with F-Active Technology for a wide range of applications. Highly concentrated, very effective and very economical to use (dilutable up to 1:200). Suitable for use in the pharmaceutical, food & drink and other industries. In addition Interflon Fin Clean All<sup>2</sup> also has been shown to have virucidal activity against enveloped viruses. The product has been tested according to NF EN14476:2013 + A2: 2019.

Interflon Fin Clean All<sup>2</sup> is included in the list by the NSF for use in the food processing industry as a general cleaner.

### Applications

Ideal universal cleaner for almost all applications, such as cleaning machines, floors and walls, etc., also in the food processing and pharmaceutical industries. Suitable for cleaning both the outside and inside of vehicles. Also suitable for removing transport wax.

### Advantages

- ⊕ Leaves no residue after rinsing
- ⊕ Economical in use
- ⊕ Biodegradable
- ⊕ Contains renewable raw materials
- ⊕ Supplied as a concentrate
- ⊕ Does not contain NTA, EDTA
- ⊕ No hazard pictograms (label-free)
- ⊕ Not ADR classified
- ⊕ Light anti-corrosive properties

### Instructions for use

Depending on the application, apply Interflon Fin Clean All<sup>2</sup> concentrated or diluted to 1:200 (see page 2 of the Technical Data Sheet for an overview of dilutions). Allow the product to work, then clean the surface with a brush, sponge or cloth. Do not allow the surface to dry because under certain circumstances a grey residue is left behind. Rinse with water. It is advisable to test the cleaner in an inconspicuous area to ensure that the cleaner does not damage the surface to be cleaned.

Apply the cleaner to vertical surfaces from bottom to top with overlaps to prevent dripping traces. To clean / remove dirt, work from top to bottom to avoid streaks.

Before cleaning with Interflon Fin Clean All<sup>2</sup> in the food processing industry, remove or cover all food products and packaging. After cleaning in the food processing industry, rinsing with drinking water is required. Never allow the product to dry and never process it in direct sunlight

Property	Result	Method
Composition	Mixture of surface-active substances, enzymes and water	-
Colour	Light yellow	-
Odour	Characteristic	-
Density 20°C	1.01 g/cm <sup>3</sup>	-
Highest application temperature	70 °C	-
pH 1 20°C	8.9	-
Biodegradability	> 60%	OECD 301D
Shelf life*	2 years	-
Vapour pressure 20°C	23.5 hPa	-
NSF registration number	158201	A1
Halal	Yes	
Kosher	Yes	

\* Shelf life of the product in original and unopened packaging. Storage temperatures <0°C need to be avoided to guarantee product quality.

Technical Data Sheet

# Interflon Fin Clean All<sup>2</sup>

Deep cleaning alkaline label-free cleaner with “1001” applications

Application table			
Applications	Interflon Fin Clean All <sup>2</sup>	Applications	Interflon Fin Clean All <sup>2</sup>
Floors <u>general</u>	1:50 - 1:200	<b>Outdoor cleaning</b>	
Workshop <u>floors</u>	1:3 - 1:50	General	1:5 - 1:100
<u>Doors</u>	1:20 - 1:200	<u>Cabin</u>	1:5 - 1:100
<u>Tables</u>	1:20 - 1:200	Chassis	1:5 - 1:100
Walls	1:20 - 1:200	<u>Tarpaulins</u>	1:5 - 1:100
Windows	1:20 - 1:200	Aluminium	1:5 - 1:100
<u>Carpets</u>	conc. - 1:20	<u>Prevents algal deposits*</u>	1:10
Steel and iron parts	1:5 - 1:100	<u>Facade frames</u>	1:10 – 1:15
Aluminium	1:5 - 1:100	<u>Subfloor</u>	1:5 - 1:100
Non-ferrous metal	1:10- 1:100	Insect remover	1:10
<u>Fly rust remover</u>	1:10- 1:100	Trams	1:5 - 1:50
Cleaner for metal- <u>washing</u> equipment	1:3- 1:100	Construction machinery	1:5 - 1:10
E.g. <u>Bubi Cleaner</u>		Containers	1:5 - 1:50
<u>Ultrasonic</u> cleaning	1:10 – 1:50	Agricultural machines	1:5 – 1:20
<b>Sanitary cleaning</b>		Grass- <u>maize-beet juice</u>	1:5 - 1:15
Floor and wall tiles etc.	1:50-1:100	<u>Vegetable and fruit juice</u>	1:10 – 1:15
<u>with disinfection and limescale removal</u>		Caravans	1:5 - 1:50
Lime, urine and limescale removal			
<b>Car wash</b>		<b>Outdoor cleaning</b>	
<u>Tile cleaning</u>	1:50-1:100	General	1:100
Outdoor <u>repellent</u>		Nicotine cleaner	Conc. – 1:10
<u>Brush washers</u>	1:5 - 1:50	<u>Glass cleaner</u>	1:1000
		<u>Cold cleaner</u>	1:3 – 1:100
		<u>Removal of preservative wax</u>	1:3
		<b>Vehicles</b>	
		<u>Rims, engine</u>	1:5 – 1:15
		<u>Bodywork</u>	1:10 – 1:30
		Engine	1:10 – 1:30
		Windows	1:70
		<u>Snow chains</u>	

This information is based on our best and present knowledge and intended to provide general notes about the product and intended use. Therefore it shouldn't be construed as guaranteeing properties of the product described or suitability for an application. Any existing industrial property rights must be observed. Quality of our products is guaranteed under our General Conditions of Sale. Interflon® and MicPol® are registered trademarks of Interflon BV. Typical properties mentioned in this document are based on our production tolerances and do not represent a specification. Variations that do not affect product performance are to be expected during normal manufacturing. Information provided in this document is subject to change without notice in advance.