

## Interflon Food Lube (aerosol)

### Highly versatile dry film lubricant for the food industry

#### Product description

Highly versatile, dry film lubricant fortified with MicPol® Technology. For a multitude of general machine parts, cables, and chain lubrication, etc. in applications within (non)food-stuff environments. Formulated to reduce your maintenance, down time costs and the number of lubricants currently in use.

Goes on wet, displaces moisture, breaks down deposits and penetrates even into the most inaccessible areas. Treats seized parts and prevents the formation rust and other corrosives. Gives a highly durable, non-staining, dry lubrication film that prevents wear on moving parts. Resistant to high pressures, resists water wash-off and will not attract dirt, dust and other abrasives.

Interflon Food Lube is listed by the NSF in accordance with DIN V 10517 for the use in applications with incidental food contact (NSF-H1) with registration number [122875](#) and ISO 21469 certified.

#### Application

For the lubrication of chains, cables, sliding tracks, joints, pivots, cams, belts, elevators, pulleys, threaded parts, bolts, rollers, taps, valves, conveyors and many other moving parts operating in food-stuff environment.

#### Advantages

- Contains MicPol® Technology for long lasting lubrication
- Reduction of friction and wear
- Dry lubrication
- Economic in use
- High penetration capacity

#### Instructions for use

Shake or stir before use according to the size of the packaging. Parts should be cleaned first with a solvent or alkaline cleaning agent. Spray Interflon Food Lube onto parts such as cables and chains and allow to penetrate. Wipe off the excess lubricant with a clean cloth. Long penetration time gives long re-lubrication intervals. Regular use of Interflon Food Lube extends the life of the chain dramatically.

Note: Do not use too much Interflon Food Lube. Applying a thin layer, with occasional re-lubrication, gives a better result than a thick layer.

#### Safety regulations

See safety data sheet.

#### Packaging

See our current article list.

#### Transport regulations

See safety data sheet.

## Interflon Food Lube (aerosol) Highly versatile dry film lubricant for the food industry

### Technical data

Property	Result	Method
Composition	Mixture of synthetic and vegetable oils, solvent, additives and MicPol®. Propellant propane, butane and isobutane.	
Colour	Light brown	
Odour	Oily	
Density @ 20°C	0.83 g/cm <sup>3</sup>	
Kinematic viscosity@ 40°C	21 cSt	ASTM D445
Pour point	-45°C	ASTM D97
Lowest application temperature	-20°C	
Highest application temperature*	180°C	
Friction coefficient	0.02-0.06 (MicPol®)	
Manufacturing date	The batch number consists of a 6-digit number. The last 4 numbers represent the MM/YY of the manufacturing.	
Shelf life**	6 years	

\* High temperature limit is valid after evaporation of solvent.

\*\* Shelf life of the product when stored at room temperature in the original and unopened packaging.

*Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice.*

---

**INTERFLON BV, P.O. Box 1070**  
**NL-4700 BB Roosendaal, The Netherlands**  
**Tel. + 31 (0) 165 55 39 11 / [www.interflon.com](http://www.interflon.com)**

---

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale. Interflon®/MicPol® is a registered trademark of Interflon BV.