

Interflon Lube HT/SF

High temperature oil with long-lasting effect

Product description

Synthetic high temperature lubricant with MicPol® Technology. Designed for the lubrication of chains and other machine parts exposed to high temperatures and extreme loads. Sets up a highly durable lubrication film that reduces friction and virtually eliminates wear. Links, hinges and bearings operate smoothly even after the lubricant layer provides lower friction which reduces head remain on the outside has disappeared. Interflon Lube HT/SF contains no volatile solvents that penetrates at high temperatures in bearings, hinges etc.

Interflon Lube HT/SF is listed by the NSF in accordance with DIN V 10517 for use on equipment and machine parts in the food industry in locations where there is no possibility of the lubricant or lubricated part contacting edible products (NSF-H2) with registration number [123400](#).

Application

Where parts are exposed to high temperatures and extreme pressure or where conventional lubricants do not last long enough. Resist high pressures and temperatures up to +245°C, even up to +270°C for short periods.

Suitable for the lubrication of chains, chain rollers, cables, pins, sprockets and many other machine parts used in food processing equipment, food packaging and logistics, baking ovens, bakery machines, mixers, drying ovens, stentor frames, muffle furnaces and printing machines as well as equipment used at brick and sandstone fabrication environments and in sterilization and coating applications.

Advantages

- For applications with a temperature up to 245°C (short 270°C)
- Long life time at high temperatures
- For heavy loaded circumstances
- Excellent penetration, also at high temperatures
- Very little smoke emission

Instructions for use

Shake or stir before use according to the size of the packaging. Parts should be cleaned first with a solvent or alkaline cleaning agent. For chain lubrication: immerse the chain for two hours in Interflon Lube HT. Apply Interflon Lube HT/SF preferably to parts when they are warm and allow to penetrate. Application can be carried out with the assistance of drop lubrication, an oil-can or with a brush. Automatic lubrication systems need to have the facilities to stir Interflon Lube HT/SF regularly. For application on cold parts, Interflon Lube HT can be used.

Safety regulations

See safety data sheet.

Packaging

See our current article list.

Transport regulations

See safety data sheet.

Interflon Lube HT/SF

High temperature oil with long-lasting effect

Technical data

Property	Result	Method
Composition	Mixture of synthetic oils, additives and MicPol®.	
Colour	Dark brown	
Odour	Nearly odourless	
Density @ 20°C	0.98 g/cm ³	
Kinematic viscosity @ 40°C	355 cSt	ASTM D445
Pour point	-22°C	ASTM D97
Lowest application temperature	-10°C	
Highest application temperature	245°C (short 270°C)	
Shelf life*	4 years	

* Shelf life of the product when stored at room temperature in the original and unopened packaging.

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice.

INTERFLON BV, P.O. Box 1070
NL-4700 BB Roosendaal, The Netherlands
Tel. + 31 (0) 165 55 39 11 / www.interflon.com

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.

Interflon®/MicPol® is a registered trademark of Interflon BV.