

Interflon Slide Wax Dry (aerosol)

Exceptionally durable lubricant for conveyor systems

Product description

Extraordinary long-lasting, low-friction slide and conveyor lubricant in a quick-drying formula. Replacement for silicone sprays. Makes it possible to slide goods with much less force, resistance and jerking on conveyors. Engineered for smoothing the sliding surfaces of manufacturing, packaging and transport equipment and conveyors in areas where food, beverages and drugs are being processed.

Formulated with MicPol® Technology and high performance resins for extraordinary adhesion, toughness, corrosion and abrasion resistance and far better slipping effect than any other lubricant, slide coating or silicone spray available to date.

Interflon Slide Wax Dry (aerosol) is listed by the NSF in accordance with DIN V 10517 for use on equipment and machine parts in the food industry in locations where there is no possibility of the lubricant or lubricated part contacting edible products (NSF-H2) with registration number [139528](#).

Application

Very effective, food-grade lubricant for smoothing slides, converging/dividing conveyors, unscramblers, accumulators, transfer-plates, feeding containers, cutting tables and other sliding surfaces of manufacturing, packaging, transport and printing equipment, in particular in areas where food, beverages and drugs are being processed.

Advantages

- Highly durable, for a much longer operating life
- Dry lubricating film; leaves no oily residue; does not grease or stain packages
- Very low friction
- Resists moist and dirt
- Does not affect paint and ink
- Harmless to stainless steel, most rubbers and plastics
- Does not contain silicones
- Aerosol can be used in every position

Instructions for use

Shake well before use. Parts should be cleaned first with a solvent or alkaline cleaning agent. Spray onto surface and let dry.

Safety regulations

See safety data sheet.

Packaging

See our current article list.

Transport regulations

See safety data sheet.

Interflon Slide Wax Dry (aerosol)

Exceptionally durable lubricant for conveyor systems

Technical data

Property	Result	Method
Composition	Mixture of waxes, solvents, additives and MicPol® . Propellant propane, butane and isobutane.	
Colour	Cloudy	
Odour	Characteristic	
Density @ 20°C	0.77 g/cm ³	
Lowest application temperature	5°C	
Highest application temperature*	60°C	
Friction coefficient	0.02-0.06 (MicPol®)	
Shelf life**	4 years	

* High temperature limit is valid after evaporation of solvent.

** Shelf life of the product when stored at room temperature in the original and unopened packaging.

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice.

INTERFLON BV, P.O. Box 1070
NL-4700 BB Roosendaal, The Netherlands
Tel. + 31 (0) 165 55 39 11 / www.interflon.com

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.

Interflon®/MicPol® is a registered trademark of Interflon BV.